

DEVIL BLUE-RED S5 SRC



DESCRIPTION	NORM EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: PVC – 8% Nitrilic rubber	5.4.2 Thickness 5.4.4 Modulus at 100 % elongation: 5.4.5 Flexing resistance:	3,10 mm 1,8 N/mm ² 296% no cracking before 150.000 flexes.	≥1,00 mm 1,3 to 4,6N/mm ² ≥ 250% no cracking before 150.000 flexes.
SAFETY TOE CAP: Steel	5.3.2.3 Impact resistance 5.3.2.4 Compression resistance	15,5 mm 15 mm	≥14 mm ≥ 14 mm
PIERCE-RESISTANCE: Stainless steel	6.2.1 Determination of penetration resistance	at 1.100 N the penetration-resistant insert doesn't show the complete penetration (PASS).	
SOLE: PVC – 8% Nitrilic rubber	5.8.2 Tear strength 5.8.3 Abrasion resistance 5.8.4 Flexing resistance 5.8.5 Hydrolysis 6.2.2.2 Antistatic Oils resistance 5.11 Pressed ceramic tile floor on detergent resistance Flat slip Heel slip Stainless steel plate on glycerin resistance Flat slip Heel slip 6.2.4 Energy absorption of seat region:	12 kN/m 178 mm ³ 2,5 mm 2,5 mm dry: 1,56 x10 ⁸ Ω wet: 8,44 x10 ⁷ Ω 8 % 0,69 0,48 0,19 0,13 21 J	≥ 8 kN/m ≤ 250 mm ³ ≤ 4,0 mm ≤ 6,0 mm tra 1,00x10 ⁵ Ω e 1,00x10 ⁹ Ω ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13 >20 J
SIZES: 36-48			

DEVIL BLUE-RED S5 SRC



DESCRIERE	NORMA EN ISO 20345:2011	RESULTAT	CERINTE NORMA
Fete: PVC-8% cauciuc nitrilic	5.4.2 Grosime 5.4.4 Rezistenta la alungire 5.4.5 Rezistenta la flexare	3.1 mm 1.8 N/mm ² 296% Fara crapare inainte de 150.000 flexari	≥1.00 mm 1,3 to 4,6N/mm ² ≥ 250% Fara crapare inainte de 150.000 flexari
Bombeu de siguranta: Otel	5.3.2.3 Rezistenta la impact 5.3.2.4 Rezistenta la compresiune	15.5 mm 15,0 mm	≥ 14 mm ≥ 14 mm
<u>Lamela antiperforare:</u> Otel inoxidabil	6.2.1 Determinarea rezistentei la penetrare	La 1.100 N inca rezista la penetrare	
Talpa: PVC-8% cauciuc nitrilic	5.8.2 Rezistenta la sfasiere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 5.8.5.Hidroliză 6.2.2.2 Antistatic 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe suprafata totala a talpii	12 kN/m 178 mm ³ 2,5 mm 2.5 mm Uscat: 1,56 x10 ⁸ Ω Umed: : 8,44 x10 ⁷ Ω 8.0% 0,69 0,48	≥ 8 kN/m ≤250mm ³ ≤ 4,0 mm ≤ 6,0 mm tra 1,00x10 ⁵ Ω e 1,00x10 ⁹ Ω ≤ 12% ≥ 0,32 ≥ 0,28

	Alunecare pe calcai		
	Rezistenta la alunecare pe placi din otel acoperite cu glicerina		
	Alunecare pe suprafata totala a talpii	0,19	$\geq 0,18$
		0,18	$\geq 0,13$
	Alunecare pe calcai		
	6.2.4 Absorbția de energie	21J	$>20 \text{ J}$
	a regiunii scaunului:		

MARIMI : 36-48

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207 www.exena.it –

info@exena.it - pec: amministrazione@pec.exena.it

Traducere din limba engleza - in conformitate cu documentul

EXENA

DECLARATIE DE CONFORMITATE UE

M22 -Vers. 00

Conform regulamentului (UE) 2016/425 – Anexa IX, **Exena srl** DECLARA
ca echipamentul individual de protectie si lotul respectiv de productie
descrie mai jos:

Articol: **DEVIL**



Este in conformitate cu standardul: EN ISO 20345:2011

Clasa: II

Categoria de marcaj: S5 SRC

Nr. certificat: F-130-05591-22

Data: 06.10.2022

EMIS DE: CIMAC – 0465

Civitanova Marche,
Aplicata parafa firmei EXENA S.R.L.
Sediul in Via Breda, 7/A
Civitanova Marche (MC), ITALIA ,

Sfârșitul traducerii

DECLARATION OF CONFORMITY UE

M22 - Ver.00

As per Regulation (UE) 2016/425 - Annex IX, Exena Srl declares that the ppe and the relative production batch below described:

item:

DEVIL

batch:



conforms to the standard:

EN ISO 20345:2011

class:

II

marking category:

S5 SRC

certificate numb.:

F-130-05591-22

date:

06/10/2022

issued by:

CIMAC - 0465

Civitanova Marche

EXENA S.r.l.
Via Breda, 7 - Z.na Ind. A
Tel. 0733 897256 Fax 0733 897519
62012 CIVITANOVA MARCHE (MC)
P.IVA 01336080435

EXENA S.r.l.

Via Breda, 7 - Z.na Ind. A 62012 - CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

P. IVA: 01336080435 - Reg. Impr. Trib. MC N. 21676/1998 - CCIAA MC 22988

www.exena.it - info@exena.it - pec: amministrazione@pec.exena.it

