

EROS BLUE S1P SRC



DESCRIERE	NORMA EN ISO 20345:2011	REZULTAT	CERINTE NORMA
Fete: Material textil+insertii TPU	5.4.3 Rezistenta la sfasiere 5.4.6 Coeficient de Permeabilitatea la vapori de apa	110 N 6.5 mg/cm ² h 53.4 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
Captuseala caputa : Material textil perforat, rezistent la abraziune, asigură respirația piciorului	5.5.1 Rezistenta la sfasiere 5.5.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat) 5.5.3 Coeficient de Permeabilitatea la vapori de apa	26 N Fara decupaj Fara decupaj 7.7 mg/cm ² 62 mg/cm ²	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm ² ≥ 20,0 mg/cm ²
Captuseala stailf: Membrană respirabilă, rezistentă la abraziune	5.5.1 Rezistenta la sfasiere 5.5.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat) 5.5.3 Coeficient de Permeabilitatea la vapori de apa	25N Fara decupaj Fara decupaj 7.5 mg/cm ² 60.6 mg/cm ²	≥ 15 N 51.200 cicluri 25.600 cicluri ≥ 2,0 mg/cm ² ≥ 20,0 mg/cm ²
Bombeau de siguranta: Material compozit nemetalic	5.3.2.3 Rezistenta la impact 5.3.2.4 Rezistenta la compresiune	14.5 mm 15.5 mm	≥ 14 mm ≥ 14 mm
Lamela antiperforare: Lamelă antiperforație nemetalică, perforație zero	5.7.1 Grosime 5.7.3 Absorbția de apa	3.5 mm 88 mg/cm ²	≥ 2,0 mm ≥ 70,0 mg/cm ²

Acoperis de brant: Talpa interioara detasabila, captusita, antistatica	5.7.4.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat)	Fara perforatii Fara perforatii	25.600 cicluri 12.800 cicluri
Talpa: PU 1D talpa aderenta, SRC	5.8.2 Rezistenta la sfasiere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 5.8.5.Hidroliză 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe suprafata totala a talpii Alunecare pe calcai Rezistenta la alunecare pe placi din otel acoperite cu glicerina Alunecare pe suprafata totala a talpii Alunecare pe calcai	10.6 kN/m 58 mm ³ 2.5 mm 1.5 mm 1% 0.5 0,44 0,21 0,16	≥ 8 kN/m ≤ 150mm ³ ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MARIMI : 35-48 MONDOPOINT 11

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519 C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207 www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

EROS BLUE S1P SRC



DESCRIPTION	NORMA EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: Printed leather	5.4.3 Tear strength 5.4.6 Water vapor permeability Coefficient	110 N 6,5 mg/cm ² h 53,4 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
VAMP LINING: Breathable, abrasion resistance.	5.5.1 Tear strength 5.5.2 Abrasion resistance(Wet) Abrasion resistance(Dry) 5.5.3 Water vapor permeability Coefficient	26 N No holes No holes 7,7 mg/cm ² h 62 mg/cm ²	≥ 15 N 25.600 cycles 12.800 cycles ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
QUARTER LINING: Breathable, abrasion resistance.	5.5.1 Tear strength 5.5.2 Abrasion resistance(Wet) Abrasion resistance(Dry) 5.5.3 Water vapor permeability Coefficient	25 N No holes No holes 7,5 mg/cm ² h 60,6 mg/cm ²	≥ 15 N 51.200 cycles 25.600 cycles ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
SAFETY TOE CAP: Steel	5.3.2.3 Impact resistance 5.3.2.4 Compression resistance	14,5 mm 15,5 mm	≥ 14 mm ≥ 14 mm
PIERCE-RESISTANCE: Stainless steel	5.7.1. Thickness 5.7.3 Water absorption	3,5 mm 88 mg/cm ²	≥ 2,0 mm ≥70,0 mg/cm ²
FOOTBED: Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance(Wet) Abrasion resistance(Dry)	No holes No holes	25.600 cycles 12.800 cycles
OUTSOLE: PU 2D, Antislip sole, SRC	5.8.2 Tear strength 5.8.3 Abrasion resistance 5.8.4 Flexing resistance 5.8.5 Hydrolysis 6.4.2 Oils resistance 5.11 Pressed ceramic tile floor on detergent resistance Flat slip Heel slip Stainless steel plate on glycerin resistance Flat slip Heel slip	10,6 kN/m 58 mm ³ 2,5 mm 1,5 mm 1.0 % 0,50 0,44 0,21 0,16	≥ 8 kN/m ≤ 150 mm ³ ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MISURE : 35-48

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207

www.exena.it – info@exena.it – pec: amministrazione@pec.exena.it

Traducere din limba engleza - in conformitate cu documentul

EXENA
DECLARATIE DE CONFORMITATE UE
M22 -Vers. 00

Conform cu cerințele esențiale stabilite în anexa II Regulamentul (UE) 2016/425,
Exena srl DECLARA ca echipamentul individual de protecție și lotul
respectiv de producție descris mai jos:

Articol: EROS BLUE S1P SRC

Standard: EN ISO 20345:2011

Clasa: II

Categoria de marcaj: S1P SRC

Nr. certificat: F-130-00781-18

Data: 03.10.2018

EMIS DE: CIMAC -0465

Civitanova Marche,

Aplicata parafa firmei EXENA S.R.L.

Sediul in Via Breda, 7/A

Civitanova Marche (MC), ITALIA ,

Semnatura ilizibila

Sfârșitul traducerii

EC DECLARATION OF CONFORMITY

The Manufacturer

EXENA SRL

Declares that the new PPE described hereafter.

EROS BLUE S1P SRC

Is in conformity with the essential requirements set out in Annex II Regulation (EU) 2016/425 and
it is identical to the PPE which is the subject of EC CERTIFICATE OF CONFORMITY N° **F-130-
00781-18** issued by

**CIMAC
C.so Brodolini, 19
27029 VIGEVANO (PV)
ITALY**

Civitanova Marche lì 03/10/2018

Giacomo Bara
Sales Coordinator
EXENA SRL

