

SHOWA

381



- Engineered yarn
- Microfibre
- Seamless knit

FEATURES

- Embossed microporous nitrile palm finish
- SHOWA engineered microfibre yarns (0.52 denier)
- High abrasion resistance level 4
- Ultra-light weight: 19 g
- Palm Thickness : 0.90mm
- Excellent fitting due to optimal liner design
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand.

BENEFITS

- Abrasion resistance lasts twice as longer as SHOWA 380 (8000 cycles vs 4000)
- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments
- The 0.84mm finger thickness provides an excellent level of tactility and sensitivity
- Microfibre properties boost vapour permeation and enhances breathability thus drier hands and less sweat
- Exceptional suppleness, ultra-comfort and hand fitting thanks to the combination of microfibre and spandex
- A flexible glove designed for easy movement and extended wear
- Seamless knit designed to prevent irritation
- Low lint with microfibre
- No latex allergy risks

INDUSTRY



Aerospace



Airports & Ports



Automotive



Construction



DIY



Engineering



Mechanical



Packaging



Warehousing & Distribution

IDEAL APPLICATIONS

- Intricate parts handling
- Light assembly of oil-coated pieces
- Mechanical engineering
- Automotive repairs and maintenance
- Mechanical and engineering
- Shuttering
- Assembly dry and oily parts
- Component Assembly

COATING

- Microporous nitrile



NORMS



SHOWA

381



PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



SIZES

- 6/S
- 7/M
- 8/L
- 9/XL
- 10/XXL



COLOUR

- Grey w/ black palm



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
380



MATERIAL
Nylon

COATING
Microporous nitrile


SHOWA
376R



MATERIAL
Nylon

COATING
Foam nitrile

SHOWA
S-TEX 581



MATERIAL
Kevlar

COATING
Microporous nitrile

[USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown.
Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands

showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved